

# Coil Lanyards with Legs

## Installation and Usage Instructions

### IMPORTANT NOTES

- If the coil has lost its memory it is best to replace the product as this is indicative that the lanyard experienced a drop.
- Never attached lanyard to a pant loop.
- Inspect prior to each use for the following and discard if found
  - There is evidence of wear
  - Lanyard experiences a drop
  - Carabiner doesn't close properly
  - Any doubt of products integrity
  - Rips, tears or excessive wear in the fabric
  - Cracks, slits or stress risers in the coil material



**NOTE:** If the coil is being pulled through the tool pocket sleeve try using the CC2956WR14L which has a longer extension leg allowing for a smooth transition into and out of the pocket.

### WARNINGS

ALWAYS WEAR APPROPRIATE PROTECTIVE EQUIPMENT. DO NOT USE THIS PRODUCT ON OR NEAR ROTATING EQUIPMENT. IMPROPER USE COULD RESULT IN DEATH OR DISMEMBERMENT. IF ANY CRACKS, RIPS OR TEARS NOTED, PRODUCT REPLACEMENT IS REQUIRED.



**1** Insert the rope end through the tool attachment D-Ring tethering point, tool tethering hole or similar tethering point. If the tool tethering hole is too small it may be necessary to use a wire rope and pliers to pull the rope through the hole. The approximate minimum tethering hole size for the rope to fit through is 3/16".

**2** Next take the carabiner and slide through the rope loop and continue pulling the entire cable until the slip knot is tight around the tool handle or the tool lanyard tether attachment.



**3** When completed the assembly should look similar to the photo.

# INSTALLATION



Ty-Flot, Inc. • 305 Massabesic Street • Manchester, NH 03103  
www.ty-flot.com • Phone: 603-669-5169 • Fax: 603-669-5113

**THE DROP STOPS HERE**