

# 100lb Zip Top Dual Load Rated Tool Bucket

## Installation and Usage Instructions

Please read instructions carefully and fully before installation and/or usage.

### IMPORTANT NOTES

- Inspect prior to every use
- Inspect connections prior to every lift
- Ensure bucket is in a secure location prior to manipulating contents
- User is responsible for determining safe lifting techniques
- Ensure bucket is closed when transferring to/ from height and when not actively being used
- To increase product life, when lowering, avoid dropping to the ground
- Ensure bucket is always attached to a truly secure attachment point

### DO NOT

- Do not shock load
- Do not load with sharp objects (figure 1) (unless properly shielded to prevent puncture)
- Do not use objects that interfere with bucket closure (figure 2)
- Do not use handles near zipper for lifting, transporting, or attaching tethers.
- Do not attach to your body



Figure 1



Figure 2

### WARNINGS

ALWAYS WEAR APPROPRIATE PROTECTIVE EQUIPMENT. DO NOT USE THIS PRODUCT ON OR NEAR ROTATING EQUIPMENT. IMPROPER USE COULD RESULT IN DEATH OR DISMEMBERMENT. IF ANY CRACKS, RIPS OR TEARS ARE NOTED, PRODUCT REPLACEMENT IS REQUIRED.

## LOADING



Attach items to the inside loops.


\*Only attach one tool to each strap. Max weight 6 lbs



Fully close zipper once all items are inside.



Lock snap hook through the zipper pull to prevent unintentional opening.



The carabiner is the only appropriate lifting point. Lift the bucket with an appropriate lifting apparatus.



Handles near the zipper are for adjusting only.

# INSTALLATION

PART NO.	INTERNAL TETHER LENGTH	MAX WT. INTERNAL TETHERS	MAX LOAD RATING
TTB300BNLBZP	11" (27.94cm)	6 lbs (2.72kg)	100 lbs (45.36kg)
TTB300BNLBZPHLP	11" (27.94cm)	6 lbs (2.72kg)	100 lbs (45.36kg)

\*Do not lift more than one bucket at a time on the same lifting rope/strap/chain.



STRONGHOLD  
BY TY-FLOT

Ty-Flot, Inc. • 305 Massabesic Street • Manchester, NH 03103  
www.ty-flot.com • Phone: 603-669-5169 • Fax: 603-669-5113